

# Floor Varnish Clean & Care

## Product properties

Special soap for cleaning and care. Recommended for cleaning and care for wood, vinyl and laminate floors. Removes impurities quickly and effectively and protects the surface from soiling. Suitable for frequent floor washing.

- Effective cleaning and care
- Protects from soiling
- Suitable for frequent floor washing



## Product use

Cleaning of lacquered wooden-, vinyl- and laminate floors.  
Can also be used for painted floors and non-absorbent tiles.

## Substrate

Must be non-absorbent and able to withstand water and alkalines, pH 8.5.

## Treatment

Mix 125 ml Clean & Care with 5L warm water.  
Repeat the treatment if the surface is extremely dirty.  
Suitable for frequent floor washing.

## Application

Mop or cloth.  
Avoid unnecessary moisturizing and formation of lakes on the surface and wipe with a wrung-out cloth.  
Always wash along the length of the wood.  
Best results are obtained by working with two buckets, one with clean soapy water and one for wringing the cloth.

## Expected result

Uniformly cleaned surface free of grease and dirt.

**Storage:** Cool, frost free and tightly closed

## Supplementary Info

Shelf life: 36 months in unopened container.

## Technical Data

Product Type	Cleaning
Density (kgs/l)	1.02
pH	8.5
Mixing ratio	125 ml to 5L water
Contains	AQUA, Quaternary ammonium compounds, C12-14-alkyl(hydroxyethyl)dimethyl, ethoxylated, chloro-PARETH-6, TRISODIUM DICARBOXYMETHYL ALANINATE, Poly(oxy-1,2-ethanediyl), $\alpha$ -(2-propylhydroxy-, CITRIC ACID, CETEARETH-10, CETEARETH-2, Pyrithione sodium (INNM), SODIUM HYDROXYMETHYL BENZISOTHIAZOLINONE, METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE.
Nominal spreading rate (m <sup>2</sup> /ltr.)	400
Min. working temp. during application and drying/curing	Min. +15°C
Recoatable at 20° C, 60 % RH (Hours)	2
Cleaning of Tools etc.	Water and soap

### Current TDS Version

April 2024

### Replaces TDS Version

March 2024